



### 6115 5" RANDOM ORBITAL SANDER

ITEM NO. 6115-0125

0,7 KG L 196 MM

5704196 019703

1



- Composite motor housing.
- Exhaust to central-vacuum system.
- Low vibration.
- Lightweight.
- Low noise level.

**TECHNICAL DATA:**

Speed:	12.000 RPM	Vibration level:	1,2 m/s <sup>2</sup>
Orbit diameter:	5 mm	Power:	0,6 HP (0,45 Kw)
Pad size:	5" (125 mm) with 8 holes	Air inlet:	1/4"
Spindle thread:	5/16"	Hose size:	3/8" (10 mm)
Noise level:	84 db(A)	Air consumption:	57 L/Min

### 6115 6" RANDOM ORBITAL SANDER

ITEM NO. 6115-0150

0,7 KG L 196 MM

5704196 034157

1



- Composite motor housing.
- Exhaust to central-vacuum system.
- Low vibration.
- Lightweight.
- Low noise level.

**TECHNICAL DATA:**

Speed:	12.000 RPM	Vibration level:	1,2 m/s <sup>2</sup>
Orbit diameter:	5 mm	Power:	0,6 HP (0,45 Kw)
Pad size:	6" (150 mm) with 6 holes	Air inlet:	1/4"
Spindle thread:	5/16"	Hose size:	3/8" (10 mm)
Noise level:	84 db(A)	Air consumption:	57 L/Min

### 6145 A BELT SANDER - 10 MM

ITEM NO. 6145-0010

5704196 029801

L 305 MM

0,9 KG

1



- Rubber comfort grip.
- Safety throttle lever.
- Rear exhaust.
- Rotating air inlet.

**TECHNICAL DATA:**

Speed:	20.000 RPM	Vibration level:	1,3 m/s <sup>2</sup>
Belt size:	10 x 330 mm	Hose size:	3/8" (10 mm)
Air inlet:	1/4"	Air consumption:	110 L/Min
Noise level:	86 db(A)		

### 6145 B BELT SANDER - 20 MM

ITEM NO. 6145-0020

5704196 029818

L 376 MM

1,5 KG

1



- Rubber comfort grip.
- Safety throttle lever.
- Rear exhaust.
- Rotating air inlet.

**TECHNICAL DATA:**

Speed:	18.000 RPM	Vibration level:	2,5 m/s <sup>2</sup>
Belt size:	20 x 520 mm	Hose size:	3/8" (10 mm)
Air inlet:	1/4"	Air consumption:	119 L/Min
Noise level:	84 db(A)		