

POLAR®MISCELLANEOUS PRODUCTS



9400 S TAPE RULES

- Precision class II. Casing in steel with rubbergrip and clip.
- Anti-reflex nylon coated tape of hardened steel.
- Corrosion-, wear- and scratching resistant. Two buttons for tape rewind.
- Rigid up to 2,4 m horizontal and 3,6 m vertical.
- Double graduation in black on yellow background.
- Decimals highlighted in red.



ITEM NO.	5704196+	L	SCALE	WIDTH MM	AxBxC MM	Ğ	3	
9400-0003	009506	3 m	mm	16	70 x 65 x 30	150	12	
9400-0005	009513	5 m	mm	25	80 x 75 x 38	300	12	
9400-0008	009520	8 m	mm	25	90 x 85 x 40	415	6	

9400 C TAPE RULE

- Precision class II. Casing in steel with rubbergrip and clip.
- Stainless hook with two magnets. Anti-reflex nylon coated tape of hardened steel.
- Corrosion-, wear- and scratching resistant. Two buttons for tape rewind.
- Rigid up to 1,8 m horizontal and 2,6 m vertical.
- Double graduation in mm and inches, black on yellow background.
- Decimals highlighted in red.



9400 P TAPE RULE


- Precision class II. Casing of shock resistant ABS with rubbergrip and stainless clip.
- Anti-reflex nylon coated tape of hardened steel.
- Corrosion-, wear- and scratching resistant. Button for tape rewind.
- Rigid up to 2,4 m horizontal and 3,6 m vertical.
- Double graduation in black on yellow background.
- Decimals highlighted in red.



I	ITEM NO.	5704196+	L	SCALE	WIDTH MM	AxBxC MM	Ĝ	3	
I	9400-1005	011257	5 m	mm	25	93 x 70 x 40 mm	250	12	


9410 P **TAPE RULE**

■ Precision class II.



Graduation in black on yellow background.







L 50 m i

SCALE n mm/cm

CALE WIDTH MM **AxBxC** MM 295 x 190 x 40 Ğ

