

OE42072: Leegmaken van de bak / Vider le bac

| Cod | Omschrijving |
|---------|---|
| OE33125 | Modulaire wandkit voor het ledigen van tanks en zwaartekrachtafvoeren uitgerust met pneumatische zuigerpomp p/n OE33070 met Viton® afdichtingen |
| OE33119 | Nippel G 1" (m) x G 3/4" (m) |
| OE33126 | Vrouwelijke snelkoppeling met terugslagklep, draad G 3/4" |
| OE33127 | Mannelijke snelkoppeling met terugslagklep, schroefdraad G 3/4" (f) |
| OE33118 | Nippel G 1/2" (m) x G 3/4" (m) |

| Cod | Description |
|---------|---|
| OE33125 | Kit modulaire mural pour la vidange de réservoirs et d'égouts par gravité équipé d'une pompe pneumatique à piston p/n OE33070 avec joints en Viton® |
| OE33119 | Raccord G 1" (m) x G 3/4" (m) |
| OE33126 | Raccord rapide femelle avec clapet anti-retour, filetage G 3/4" |
| OE33127 | Raccord rapide mâle avec clapet anti-retour, filetage G 3/4" (f) |
| OE33118 | Raccord G 1/2" (m) x G 3/4" (m) |



DRAINING KIT

P/N OE33125

Wall-mounted draining kit, equipped with: ► P/N OE33070 pump R 1:1 - 23 l/min - Viton® seals ► P/N OE33115 wall bracket ► P/N OE38026 flexible suction hose ► P/N OE37803 air inlet flow regulator

► No.1 packing m³ 0,029 ► kg 8,4

| P/N (with Viton® seals) | | OE33125 |
|---------------------------|-------|---------|
| Ratio | | 1:1 |
| Flow rate | l/min | 23 |
| Pump | P/N | OE33070 |
| Flexible suction tube 2 m | P/N | OE38026 |
| Air inlet flow regulator | P/N | OE37803 |
| Wall bracket | P/N | OE33115 |

| STANDARD WASTE OIL DRAINER | PIT WASTE OIL DRAINER | FLOOR WASTE OIL DRAINER |
|---|--|--|
| <p>1</p> <p>P/N OE33134 P/N OE33127 P/N OE33118</p> | <p>2</p> <p>P/N OE33119 P/N OE33127 P/N OE33134</p> | <p>3</p> <p>P/N OE33134 P/N OE33127 P/N OE33118</p> |
| <p>To connect waste oil drainers with above mentioned emptying kit it is necessary to mount a male quick coupler. Depending on the kind of waste oil drainers (standard, for pit or floor mounted) a different nipple must be used as shown in the examples (Pic. 1 - 2 - 3).</p> | | |